




Preventive Maintenance It Is About Money

Proven cost savings with the only product-line used
from nuclear submarines to the Space Shuttle. Why?
One word – Quality.



Inside
Rudders



Tugboat ✿ Workboat ✿ Barge ✿ Dredge ✿ Fishing Vessel ✿ Floating Drydocks

- Anchor Chains–Lockers–Windlass
- Wire–Rope–Winches
- Cranes–Hoists–Rails
- Spoons–Stabilizers
- Hawsers–Hatch Coamings
- Offshore Platform Mach. & Tools
- Equipment–Vehicles–On–Deck Cargo
- Container Guides
- Elevator Guide Rails
- Open Gears
- Cables & Electric Connectors
- Ballast Tanks
- Voids–Skegs
- Bilges–Keels
- Stern Tubes
- Pontoons
- Caissons
- Undersea Equipment
- Hatch Covers
- Water Tight Door Dogs
- Locks & Hinges
- Grey Water Tanks



NOTHING LASTS LONGER
Environmentally Friendlier
No Solvents



Australian Agent

Unit 1, 19 Balook Drive
Beresfield NSW 2322
Phone 02 4966 8020
Fax 02 4966 8302
www.stottind.com.au

The only product-line used from nuclear submarines to the Space Shuttle.

**Available in liquid, gel, and grease forms. ✿ Penetrates to base metal and cable core.
Displaces rust. Where surfaces are heavily corroded acts as descaler.**

National stock numbers listed where applicable to type of FLUID FILM and container size.

Tank Coatings, Rudder, and Void Preservatives, Appendage Protection

FLUID FILM Liquid A

Applied by spray, flotation, fill and drain, or brush. Use as a descaler over heavily corroded surfaces. Up to 2 years service.

NSN-8030-01-387-1051	5-gal. pail (20 liter)
NSN-8030-01-386-3877	1-gal. 4/case

FLUID FILM Liquid AR (semi-liquid)

Applied by spray or brush over moderately corroded surfaces after removal of thick rust scale. Up to 3-5 years service.

NA	5-gal. pail (20 liter)
NSN-8030-01-381-7311	1-gal. 4/case

FLUID FILM Gel BW

Applied by spray or brush over rusted surfaces. Long term protection. Up to 3-10 years service; submersibles to 20 years.

NA	5-gal. pail (20 liter)
----	------------------------

FLUID FILM Gel BEW

Applied to external appendages and components by brush.

NSN-8030-01-381-3160	5-gal. pail (20 liter)
----------------------	------------------------

Wire Rope Dressings

FLUID FILM Liquid A

Applied by lubricator, glove, or dipping. Core penetration without lubricator.

NSN-8030-01-387-1051	5-gal. pail (20 liter)
NSN-8030-01-386-3877	1-gal. 4/case

FLUID FILM WRO-EP (extreme pressure)

Government specification Mil-G018458 (SH) applied by lubricator or glove.

NSN-9159-00-530-6814	35 lb. pail (15.5 kg)
----------------------	-----------------------

General Maintenance Aerosol/Non-Aerosol

FLUID FILM AS (aerosol)

NSN-8030-01-387-1131	11-3/4 oz. 12/case
----------------------	--------------------

FLUID FILM NAS (non-aerosol)

NSN-8030-01-381-6357	12 oz. 12/case
NSN-8030-01-386-3871	1-gal. 4/case
NSN-8030-01-387-1070	5-gal. pail (20 liter)